

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 113 195 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.07.2001 Bulletin 2001/27

(51) Int Cl.7: F16H 59/08

(21) Application number: 00127352.3

(22) Date of filing: 13.12.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- Murase, Yoshitaka
Anjo-shi, Aichi-ken 444-1192 (JP)
- Eishima, Hitotoshi
Anjo-shi, Aichi-ken 444-1192 (JP)
- Takemoto, Kazuo
Anjo-shi, Aichi-ken 444-1192 (JP)
- Ohkoshi, Naoki
Anjo-shi, Aichi-ken 444-1192 (JP)

(30) Priority: 27.12.1999 JP 37150999


(71) Applicant: AISIN AW CO., LTD.
Anjo-shi Aichi 444-1192 (JP)

(72) Inventors:
• Kusafuka, Muneo
Anjo-shi, Aichi-ken 444-1192 (JP)

(74) Representative:
Leson, Thomas Johannes Alois, Dipl.-Ing. et al
Patentanwälte
Tiedtke-Bühling-Kinne & Partner,
Bavariaring 4
80336 München (DE)

(54) Range selection apparatus for an automatic transmission

(57) A range switchover apparatus is disclosed, including a detent mechanism (8) for holding in respective shift positions a range switchover means operating unit (7) capable of switching over a switchover means, which switches over a shift range, among respective shift positions, a driving force stopping unit (31,18/31,19) for preventing a driving force from the drive motor (12) from being transmitted to the range switchover means operating unit, a stoppage controlling unit (31,28) adapted to detect a position of the range switchover means operating unit to control the driving force stopping unit so as to hold the range switchover means operating unit in a predetermined shift position of the detent mechanism, an environment detecting unit (24,27) for detecting an environment of the drive motor, and a rotation controlling unit for controlling the drive motor at a predetermined rotational speed in response to a state of the environment detected by the environment detecting unit. The range switchover apparatus enables surely performing switchover of a switchover means of an automatic transmission.



Description

BACKGROUND OF THE INVENTION

1. Field of the Invention:

[0001] This invention relates to a range switchover apparatus for use in switchover of a running range of an automatic transmission.

2. Description of the Related Art:

[0002] Conventionally, a range switchover apparatus for switchover of a running range of an automatic transmission comprises a manual valve in the automatic transmission, and a shift lever connected to the manual valve by a shift cable and provided in a vehicle interior. This range switchover apparatus is constructed such that a driver operates the shift lever to there by switch over the manual valve via the shift cable. However, it has been demanded to increase freedom for a place where a shift lever is installed, at the request of a recent increase in freedom for a vehicle interior design in automobiles and of an increase in types of a car derived from the same platform.

[0003] A range switchover apparatus, which meets with such demand, is disclosed in Japanese Patent Laid-Open No. 190180/1995 and so on. With such range switchover apparatus, a motor is used to actuate a manual valve to perform switchover of running ranges, and driving of the motor is stopped upon detection of the manual valve being put in a target position.

[0004] However, since conventional range switchover apparatuses are controlled independently of the rotational speed of the motor, in the case where the rotational speed of the motor is too great, the target position is in some cases passed considerably due to an increase in inertial forces of respective constituent members even when the manual valve stops the motor at the target position.

SUMMARY OF THE INVENTION

[0005] The invention has its object to provide a range switchover apparatus capable of surely performing a switchover of a switchover means of an automatic transmission.

[0006] The above-mentioned problems are solved by a range switchover apparatus for automatic transmissions, according to a first aspect, comprising a range switchover means operating unit capable of switching over a switchover means, which switches over a shift range, among respective shift positions, a detent mechanism for holding the range switchover means operating unit in the respective shift positions, a drive motor for driving the range switchover means operating unit, a driving force stopping unit for preventing a driving force from the drive motor from being transmitted to the range

switchover means operating unit, a stoppage controlling unit adapted to detect a position of the range switchover means operating unit to control the driving force stopping unit so as to hold the range switchover means operating unit in a predetermined shift position, an environment detecting unit for detecting an environment of the drive motor, and a rotation controlling unit for controlling the drive motor at a predetermined rotational speed in response to a state of the environment detected by the environment detecting unit.

[0007] The invention according to a second aspect comprises a range switchover apparatus for automatic transmissions wherein the detent mechanism comprises a plurality of recesses provided on the range switchover means operating unit to correspond to the shift positions, and an engagement member capable of selectively engaging with and disengaging from the recesses, and the engagement member detects a position corresponding to an inlet of a recess corresponding to the predetermined shift position whereby the stoppage controlling unit transmits a stoppage signal to the driving force stopping unit.

[0008] The invention according to a third aspect comprises a range switchover apparatus for automatic transmissions wherein the driving force stopping unit stops the drive motor and actuates a brake.

[0009] The invention according to a fourth aspect comprises a range switchover apparatus for automatic transmissions wherein the driving force stopping unit comprises a clutch for cutting off a driving force from the drive motor to the switchover means driving unit.

[0010] The invention according to a fifth aspect comprises a range switchover apparatus for automatic transmissions wherein the environment detecting unit comprises a voltage measuring device for measuring an electric source voltage of the drive motor.

[0011] The invention according to a sixth aspect comprises a range switchover apparatus for automatic transmissions wherein the environment detecting unit comprises a temperature measuring device for measuring an oil temperature in the automatic transmission.

BRIEF DESCRIPTION OF DRAWINGS

[0012] The invention will be described in conjunction with the following drawings in which like features are designated with like reference characters, and wherein:

Fig. 1 is a diagrammatic view showing an entire range switchover apparatus according to a first embodiment of the invention;

Fig. 2 is an enlarged view showing a detent lever;

Fig. 3 is a table indicating a duty ratio of a motor on the basis of a battery voltage and a temperature of a working oil in an automatic transmission;

Fig. 4 is an operation flowchart of the range switchover apparatus of Fig. 1;

Fig. 5 is a view illustrating the operation of a detent

mechanism in the range switchover apparatus of Fig. 1;

Fig. 6 is a diagrammatic view showing an entire range switchover apparatus according to a second embodiment of the invention;

Fig. 7 is an operation flowchart of the range switchover apparatus of Fig. 6;

Fig. 8 is a view illustrating the operation of a detent mechanism in the range switchover apparatus of Fig. 6; and

Fig. 9 is a view illustrating inlets corresponding to a rotating direction of the detent lever.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0013] When the drive motor (12) is started, the range switchover means operating unit (7) is actuated toward desired shift positions (P, R, N, D, L) to switch over the switchover means (2, 5). Simultaneously, the detent mechanism (8) repeats the operations of holding and releasing the range switchover means operating unit (7) in a shift position (P, R, N, D, L), which the range switchover means operating unit (7) passes until it is switched over to the respective shift positions (P, R, N, D, L). Each time the range switchover means operating unit (7) is switched over to the respective shift positions (P, R, N, D, L), such switchover is detected by the stoppage controlling unit (31, 28).

[0014] When the range switchover means operating unit (7) is switched over to a desired shift position (P, R, N, D, L), the stoppage controlling unit (31, 28) actuates the driving force stopping unit (31 and 18, or 31 and 19) to prevent a driving force from the drive motor (12) to the switchover means driving unit (7). The range switchover means operating unit (7) stops the switchover operation of the switchover means (2, 5), and is held in a desired shift position (P, R, N, D, L) by the detent mechanism (8). Thus, the range switchover apparatus (1 or 100) has switched over the automatic transmission to a desired shift position.

[0015] However, the rotational speed of the motor 12 changes depending upon the environment, such as fluctuation in battery voltage, a temperature of the working oil in the automatic transmission and the like. Meanwhile, a time-lapse during deceleration and stoppage is inevitable due to inertia of respective parts until the range switchover means operating unit (7) actually stops after the driving force stopping unit (31 and 18, or 31 and 19) such as a brake, clutch or the like is actuated to prevent a driving force from the drive motor (12) to the switchover means driving unit (7). Such time-lapse varies depending upon the rotational speed of the motor, and so the detent mechanism (8) cannot in some cases hold the range switchover means operating unit (7) in a desired shift position (P, R, N, D, L) correctly depending upon the duration of deceleration and stoppage.

[0016] Hereupon, the rotation controlling unit (20) ad-

justs the drive motor (12) so as to make the same rotate at a predetermined rotational speed, as by changing the duty ratio of the drive motor (12) in response to a change in the environment, detected by the environment detecting unit (24, 27). Thereby, the duration of deceleration and stoppage becomes constant at all times, and so the detent mechanism (8) correctly holds the range switchover means operating unit (7) in a desired shift position (P, R, N, D, L).

[0017] In addition, signs in parenthesis are marked for convenience and easy correspondence with the drawings, and are not intended for limitation of the constitution of the invention.

[0018] A range switchover apparatus according to embodiments of the invention will be explained with reference to the drawings.

(First Embodiment)

(Explanation of Constitution)

[0019] Fig. 1 is a diagrammatic view of a range switchover apparatus 1 of an automatic transmission. The range switchover apparatus 1 is adapted to actuate a manual valve 2, which serves as a switchover valve constituting a part of an automatic transmission such as multistage type automatic transmissions and continuously variable transmissions (CVT). The manual valve 2 is contained in a valve body 3, which constitutes a part of an automatic transmission. The manual valve 2 is provided within the valve body 3 to be movable in directions indicated by an arrow A and an arrow B, corresponding to an axial direction of a spool 2a of the valve. The automatic transmission can be sequentially switched over to P, R, N, D and L ranges from a side of the arrow B to a side of the arrow A in the figure by moving the manual valve 2 in a direction of the arrow A and in a direction of the arrow B. An engagement groove 2c composed of two circular disks 2b, 2b is formed on a tip end of the manual valve 2 on the side of the arrow A. A detent lever (range switchover valve operating unit) 5 engages with the engagement groove 2c via a pin 5a provided on an arm portion 5B of the detent lever 5.

[0020] The detent lever 5 has a sheet-shaped body 5c as shown in Fig. 3. Five range engagement grooves 5d, 5e, 5f, 5g and 5h are formed at predetermined spacings on an upper portion of the body 5c as viewed in the figure. The respective range engagement grooves 5d, 5e, 5f, 5g and 5h are arranged in this order from a right side in the figure to correspond to the ranges "P", "R", "N", "D" and "L" of the automatic transmission. Also, the arm portion 5b provided with the above-mentioned pin 5a projects rightward of the body 5c as viewed in the figure. A parking rod engaging hole 5i for driving of a parking mechanism in the P range (not shown) is formed on and extended through a leftward portion of the body 5c as viewed in the figure. Also, a rectangular-shaped engagement hole 5j, through which a range control shaft

7 described later is inserted, is formed on and extended through a substantially central portion of the body.

[0021] Provided on an upper portion of the five range engagement grooves 5d, 5e, 5f, 5g and 5h of the body 5c is a detent spring 9 composed of a sheet spring and fixed at one end thereof to the valve body 3 or a casing of the automatic transmission or the like. A roller 9a (engagement member) rotatably supported on a tip end of the detent spring 9 is biased downward in Fig. 1 by the elasticity of the detent spring 9 to fit into and engage with one of five range engagement grooves 5d, 5e, 5f, 5g and 5h. Also, the rod-shaped range control shaft 7 engages with the engagement hole 5j of the body 5c to be made integral with the detent lever 5. The detent lever 5, the detent spring 9 and so on constitute a detent mechanism 8.

[0022] The range control shaft 7 is formed at its left tip end with an engaging portion 7a having a rectangular-shaped cross section. A valve drive device 10 is connected to the engaging portion 7a. The valve drive device 10 is mounted on a cover of the automatic transmission or the like. The valve drive device 10 has a box-shaped casing 11. The casing 11 mounts thereon a DC drive motor 12. The drive motor 12 is provided with a brake 19 for rapidly stopping the rotation of the motor. A worm 12b is mounted on an output shaft of the drive motor 12. The worm 12b meshes with a worm wheel (not shown), which is rotatably supported on the casing 11. A gear 15 is provided on the worm wheel to rotate together with the worm wheel (not shown).

[0023] A large gear 16a of a two-stage gear 16 rotatably supported on the casing 11 can mesh with the gear 15. The two-stage gear 16 comprises a small gear 16b having a half of a pitch circle radius of the large gear 16a and the large gear 16a formed therewith to be coaxial and integral therewith.

[0024] The small gear 16b meshes with an output gear (not shown), which has a pitch circle radius four times that of the small gear 16b. The output gear is rotatably supported on the casing 11. Further, the output gear is formed centrally thereof with a rectangular-shaped engagement hole 17a. The above-mentioned engaging portion 7a of the range control shaft 7 fits into and engages with the engagement hole 17a.

[0025] Connected to the drive motor 12 and the brake 19 is a range control unit (rotation controlling unit) 20 for controlling the entire range switchover apparatus 1. The range control unit 20 is connected to a shift lever position detecting unit 21. The shift lever position detecting unit 21 is connected to a shift lever 22. Connected to the range control unit 20 is a voltage meter (environment detecting unit) 24 for measuring a voltage of a battery 23 connected to the motor 12.

[0026] Further, connected to the range control unit 20 is an automatic transmission control unit 26 for controlling an automatic transmission 25. Connected to the automatic transmission control unit 26 is an oil temperature sensor (environment detecting unit) 27, which is provided

in the automatic transmission 25 to measure a temperature of a working oil in the automatic transmission 25. Also, connected to the range control unit 20 is a position sensor (stoppage controlling unit) 28, which is provided on a stationary member (not shown) to detect positions of the range engagement grooves 5d, 5e, 5f, 5g and 5h of detent lever 5. The position sensor 28 detects a body 36 being detected, provided on inlets, described later, of the respective range engagement grooves 5d, 5e, 5f, 5g and 5h to detect the range engagement grooves 5d, 5e, 5f, 5g and 5h.

[0027] The range control unit 20 comprises, as shown in Fig. 3, a RAM 1 (29) for storing a battery voltage measured by the voltage meter 24, a RAM 2 (30) for storing an oil temperature in the automatic transmission 25, measured by the oil temperature sensor 27, and a CPU (driving force stopping unit, stoppage controlling unit) 31 for storing a duty ratio of the motor 12 and controlling the rotational speed of the motor 12 on the basis of the duty ratio and for controlling the operation of the brake 1.

(Explanation of Operation)

[0028] An explanation will be given on the basis of a flowchart shown in Fig. 4.

[0029] At the start of or during the running of a vehicle, when the shift lever 22 is switched over, the shift lever position detecting unit 21 detects a switchover position of the shift lever 22 to inform the CPU 31 of the range control unit 20 of the same (section S1). The CPU 31 starts the motor 12 so as to rotate the detent lever 5 to a position where the range engagement grooves 5d, 5e, 5f, 5g, 5h corresponding to ranges corresponding to switchover positions of the shift lever can engage with the roller 9a (section S2).

[0030] At this time, information about battery voltage measured by the voltage meter 24 is stored in the RAM1 (29), and information about temperature of the working oil in the automatic transmission 25, measured by the oil temperature sensor 27 is stored in the RAM2 (30).

[0031] The CPU 31 sets a duty ratio from the information about battery voltage and the information about oil temperature on the basis of TABLE of duty ratio shown in Fig. 3 (section S3). In addition, the duty ratio is a ratio of a movable time to a total time, for example, in a given time. The motor 12 rotates forward or rearward at a rotational speed corresponding to the duty ratio (section S4). Then the range control shaft 7 rotates a predetermined angle in a direction of an arrow C or an arrow D in Fig. 1 through the worm 12b, worm wheel (not shown), gear 15, two-stage gear 16, and output gear (not shown). The detent lever 5, pin 5a, and the arm port ion 5b also rotate in the direction of the arrow C or the arrow D. When the pin 5a has rotated a predetermined angle, the spool 2a of the manual valve 2 engaging with the pin 5a via the engagement groove 2c is moved in a direction of the arrow A or the arrow B. The range of the

manual valve 2 is sequentially switched over to the P - R - N - D - L ranges from the side of the arrow B.

[0032] In the course of such switchover, the position sensor 28 sequentially detects the range engagement grooves 5d, 5e, 5f, 5g and 5h, which engage with the roller 9a. When the position sensor 28 has detected the range engagement groove corresponding to the switchover range of the shift lever 21 (section S5), the CPU 31 cuts off an electric source to the motor 12 to actuate the brake 18 (section S6) to stop the motor 12. Accordingly, the manual valve 2 is switched over to a range corresponding to the switchover range of the shift lever 21.

[0033] An operation characteristic of a feature of the embodiment will be explained below.

[0034] In the operation, when the CPU 31 stops the motor 12 with the brake 18, the detent lever 5 stops its rotation. During a time interval until the detent lever 5 actually stops its rotation after the motor 12 is stopped, the detent lever 5 may rotate due to inertia of respective parts and stop its rotation before the roller 9a falls down into a valley of the range engagement groove or after the roller passes a valley of the range engagement groove. In such case, range switchover of the manual valve 2 may become incorrect and so switchover operation of the automatic transmission 25 may not be effected smoothly.

[0035] The range switchover apparatus 1 according to the embodiment takes account of inertia of respective parts such that when the detent lever 5 rotates in a direction of an arrow D as shown in Fig. 5, the position sensor 28 detects the roller 9a being caused by the elastic force of the detent spring 9 to pass a position where the detent lever 5 is drawn in, and an inlet 5f' of the range engagement groove (for example, the range engagement groove designated by a character 5f) coming to the roller 9a, and cuts off an electric source to the motor 12 to actuate the brake 18, thereby causing a valley 5f'' to bear the roller 9a.

[0036] In addition, since it is difficult for the valley 5f'' to surely bear the roller, the range engagement groove 5f bears the roller 9a in some region (a detent lever rotation stopping region W) around the valley 5f''. The region W is set in a range of error in range switchover of the manual valve 2, and is one, in which oil pressure is generated due to the range switchover of the manual valve 2.

[0037] However, even when timing for stopping the motor 12 is set taking account of inertia of respective parts, the roller 9a cannot be in some cases born within the detent lever rotation stopping region W because the rotational speed of the motor 12 changes due to changes in the environment, such as fluctuation in battery voltage, influences due to heat of the working oil in the automatic transmission and the like.

[0038] In order to prevent such inconvenience, with the range switchover apparatus 1 according to the invention, in section S2 and section S3 the CPU 31 further

selects a duty ratio in Fig. 3 in accordance with the battery voltage and the oil temperature in the automatic transmission to control the rotational speed of the motor 12 on the basis of the duty ratio and to actuate the brake 18 in a correction region H for the braking position shown in Fig. 5 to surely bear the roller 9a within the detent lever rotation stopping region W.

(Second Embodiment)

[0039] While the range switchover apparatus 1 according to the first embodiment stops the motor and actuate the brake when rotation of the detent lever 5 should be stopped, a range switchover apparatus 100 according to a second embodiment provides a clutch (driving force stopping unit) 19 in place of the brake, and stops the rotation of the detent lever 5 by releasing the clutch 19 and cutting off transmission of driving force of the drive motor.

[0040] In addition, the range switchover apparatus 100 according to the second embodiment is constructed such that the clutch 19 is provided in place of the brake 18 in contrast to the range switchover apparatus 1 according to the first embodiment and the CPU 31 controls releasing and actuation of the clutch 19, and so the same parts as those in the range switchover apparatus 1 according to the first embodiment are designated by the same characters with an explanation thereof being omitted.

(Explanation of Operation)

[0041] An explanation will be given on the basis of a flowchart shown in Fig. 7.

[0042] At the start of or during the running of a vehicle, when the shift lever 22 is switched over, the shift lever position detecting unit 21 detects a switchover position of the shift lever 22 to inform the CPU 31 of the range control unit 20 of the same (section S11). The CPU 31 starts the motor 12 so as to rotate the detent lever 5 to a position where the range engagement grooves 5d, 5e, 5f, 5g, 5h corresponding to ranges corresponding to switchover positions of the shift lever can engage with the roller 9a (section S12).

[0043] At this time, information about battery voltage measured by the voltage meter 24 is stored in the RAM1 (29), and information about temperature of the working oil in the automatic transmission 25, measured by the oil temperature sensor 27 is stored in the RAM2 (30).

[0044] The CPU 31 sets a duty ratio from the information about battery voltage and the information about oil temperature on the basis of TABLE of duty ratio shown in Fig. 3 (section S13). The motor 12 rotates forward or rearward at a rotational speed corresponding to the duty ratio (section S14). Then torque of the motor is transmitted to the worm 12b, worm wheel (not shown), gear 15, two-stage gear 16, output gear (not shown) and the range control shaft 7. And the spool 2a of the manual

valve 2 is moved in a direction of the arrow A of or the arrow B of the pin 5a, The range of the manual valve 2 is sequentially switched over to the P - R - N - D - L ranges from the side of the arrow B.

[0045] In the course of such switchover, the position sensor 28 sequentially detects the range engagement grooves 5d, 5e, 5f, 5g and 5h, which engage with the roller 9a. When the position sensor 28 has detected the range engagement groove corresponding to the switchover range of the shift lever 21 (section S15), the CPU 31 releases the clutch 19 (section S19) to stop the motor 12. Accordingly, the manual valve 2 is switched over to a range corresponding to the switchover range of the shift lever 21.

[0046] An operation characteristic of a feature of the embodiment will be explained below.

[0047] In the operation, when the CPU 31 releases the clutch 19, transmission of the driving force of the drive motor is cut off, and the detent lever 5 stops its rotation. During a time interval until the detent lever 5 actually stops its rotation after the clutch 19 is released, the detent lever 5 may rotate due to inertia of respective parts and stop its rotation without the roller 9a surely falling down into a valley of the range engagement groove.

[0048] The range switchover apparatus 100 according to the embodiment also takes account of inertia of respective parts such that as shown in Fig. 5, the position sensor 28 detects the inlet 5f' of the range engagement groove (for example, the range engagement groove designated by a character 5f) coming to the roller 9a so that the roller 9a is born in some region (a detent lever rotation stopping region W) around the valley 5f'' of the range engagement groove 5f.

[0049] However, because the rotational speed of the motor 12 changes due to changes in the environment, such as fluctuation in battery voltage, influences due to heat of the working oil in the automatic transmission and the like, in section S12 and section S13 shown in Fig. 3 the CPU 31 selects a duty ratio in Fig. 3 in accordance with the battery voltage and the oil temperature in the automatic transmission to control the rotational speed of the motor 12 on the basis of the duty ratio. Therefore, the range switchover apparatus 100 according to the invention actuates the clutch 19 in a correction region G for the clutch release position shown in Fig. 8 to surely bear the roller 9a within the detent lever rotation stopping region W.

[0050] In addition, while an explanation has been given to the operation in the case where the detent lever 5 in the range switchover apparatuses 1, 100 according to the first and second embodiments rotates in the direction of the arrow D, it rotates in some cases in the direction of the arrow C. In Fig. 9, a position of the detent lever 5 relative to the roller 9a at the time of actuation of the brake and at the time of release of the clutch is in the vicinity of a point E (in the vicinity of inlets 5d', 5e', 5f', 5g' and 5h') in the case where the detent lever 5 ro-

tates in the direction of, the arrow D, and is in the vicinity of a point J (in the vicinity of the inlets 5d' , 5e' , 5f' , 5g' and 5h') in the case where the detent lever rotates in the direction of the arrow C. In addition, the range engagement groove indicated by the character 5d is formed to have a valley of greater depth than that of the other range engagement grooves.

[0051] Further, because the detent lever 5 is biased by the roller 9a, which is provided on the detent spring 9 with elasticity, it seems that in the case where the roller 9a abuts against an inclined surface of the range engagement groove, the detent lever is exerted by the bias of the roller 9a to rotate to enable bearing the roller 9a on the valley of the range engagement groove. However, the detent lever hardly rotates biased by the roller 9a because there is provided the worm 12b for decelerating the rotation of the motor 12.

[0052] According to the invention of the first aspect, the rotation controlling unit adjusts the drive motor so as to make the same rotate at a predetermined rotational speed in response to a state of the environment detected by the environment detecting unit, whereby after the driving force stopping unit prevents transmission of a driving force from the drive motor to the range switchover valve operating unit, the detent mechanism can correctly hold the range switchover valve operating unit in a desired shift position to surely and smoothly perform a shift range switchover of the automatic transmission.

[0053] In the case where as in the invention of the second aspect, the stoppage controlling unit transmits a stoppage signal to the driving force stopping unit when the engagement member in the detent mechanism detects a position corresponding to an inlet of a recess corresponding to a predetermined shift position, the detent mechanism can correctly hold the range switchover valve operating unit in a desired shift position to correctly perform switchover of the switchover valve even when a driving force from the drive motor is not transmitted to the range switchover valve driving unit and the range switchover valve driving unit does not stop instantly.

[0054] In the invention of the third aspect, when the driving force stopping unit stops the drive motor and actuates the brake, the switchover valve can be correctly performed by rapidly stopping the drive motor and correctly holding the range switchover valve operating unit in a desired shift position.

[0055] As in the invention of the fourth aspect, in the case where the driving force stopping unit is a clutch for cutting off a driving force from the drive motor to the switchover valve driving unit, the range switchover valve operating unit can be correctly held in a desired shift position to correctly perform switchover of the switchover valve.

[0056] A range switchover apparatus is disclosed, including a detent mechanism for holding in respective shift positions a range switchover means operating unit capable of switching over a switchover means, which switches over a shift range, among respective shift po-

sitions, a driving force stopping unit for preventing a driving force from the drive motor from being transmitted to the range switchover means operating unit, a stoppage controlling unit adapted to detect a position of the range switchover means operating unit to control the driving force stopping unit so as to hold the range switchover means operating unit in a predetermined shift position of the detent mechanism, an environment detecting unit for detecting an environment of the drive motor, and a rotation controlling unit for controlling the drive motor at a predetermined rotational speed in response to a state of the environment detected by the environment detecting unit. The range switchover apparatus enables surely performing switchover of a switchover means of an automatic transmission.

Claims

1. A range switchover apparatus for automatic transmissions, comprising:

a range switchover means operating unit capable of switching over a switchover means, which switches over a shift range, among respective shift positions;
 a drive motor for driving the range switchover means operating unit;
 a driving force stopping unit for preventing a driving force from the drive motor from being transmitted to the range switchover means operating unit;
 a stoppage controlling unit adapted to detect a position of the range switchover means operating unit to control the driving force stopping unit so as to hold the range switchover means operating unit in a predetermined shift position;
 an environment detecting unit for detecting an environment of the drive motor; and
 a rotation controlling unit for controlling the drive motor at a predetermined rotational speed in response to a state of the environment detected by the environment detecting unit.

2. The range switchover apparatus for automatic transmissions according to claim 1, wherein the range switchover means comprises a detent mechanism for holding the range switchover means operating unit in the respective shift positions, the detent mechanism comprises a plurality of recesses provided on the range switchover means operating unit to correspond to the shift positions, and an engagement member capable of selectively engaging with and disengaging from the recesses, and the engagement member detects a position corresponding to an inlet of a recess corresponding to the predetermined shift position whereby the stoppage controlling unit transmits a stoppage signal to

the driving force stopping unit.

3. The range switchover apparatus for automatic transmissions according to claim 1, wherein the driving force stopping unit stops the drive motor and actuates a brake.
4. The range switchover apparatus for automatic transmissions according to claim 1, wherein the driving force stopping unit comprises a clutch for cutting off a driving force from the drive motor to the switchover means driving unit.
5. The range switchover apparatus for automatic transmissions according to claim 1, wherein the environment detecting unit comprises a voltage measuring device for measuring an electric source voltage of the drive motor.
6. The range switchover apparatus for automatic transmissions according to claim 1, wherein the environment detecting unit comprises a temperature measuring device for measuring an oil temperature in the automatic transmission.

Fig. 1






Fig 2




<i>H (%)</i>	<i>C (V)</i>		8	10	12	14	16
	<i>B (°C)</i>						
	-40		90	90	90	90	80
	-20		90	90	90	90	80
	0		90	90	90	90	60
	20		90	90	80	90	40
	80		90	90	80	70	40
	120		90	90	80	60	40

Fig. 3

Fig. 4








Fig. 7





Fig. 8






Fig. 9



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 12 7352

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 444 676 A (MAZDA MOTOR) 4 September 1991 (1991-09-04) * column 7, line 58 - column 8, line 2 * * column 10, line 16 - column 10, line 30 * * column 40, line 39 - column 40, line 43 * * column 58, line 15 - column 58, line 23 * * figures 1,2A,17D *	1-5	F16H59/08
A	---	6	
A	EP 0 432 507 A (MAZDA MOTOR) 19 June 1991 (1991-06-19) * page 4, line 19 - page 4, line 23 * ---	1,2,4	
A	PATENT ABSTRACTS OF JAPAN vol. 007, no. 207 (M-242), 13 September 1983 (1983-09-13) & JP 58 105828 A (HONDA GIKEN KOGYO KK), 23 June 1983 (1983-06-23) * abstract * -----	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			F16H
The present search report has been drawn up for all claims			
Place of search:		Date of completion of the search	Examiner
BERLIN		30 March 2001	Kyriakides, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 12 7352

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-03-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0444676 A	04-09-1991	JP 2898045 B	31-05-1999
		JP 3255252 A	14-11-1991
		DE 69100216 D	09-09-1993
		DE 69100216 T	18-11-1993
		KR 9504311 B	28-04-1995
		US 5094115 A	10-03-1992
EP 0432507 A	19-06-1991	JP 2878342 B	05-04-1999
		JP 3157565 A	05-07-1991
		JP 2933956 B	16-08-1999
		JP 3157227 A	05-07-1991
		JP 4173432 A	22-06-1992
		DE 69029960 D	27-03-1997
		DE 69029960 T	05-06-1997
		KR 9402590 B	26-03-1994
		US 5156243 A	20-10-1992
JP 58105828 A	23-06-1983	JP 1488236 C	23-03-1989
		JP 63037729 B	27-07-1988

EPO FORM P4456

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82